



# Perfectly Warm™

**Tile Floor Heat Cable** (for use with uncoupling membranes).

The Perfectly Warm Cable is a custom designed cable compatible with all uncoupling membranes. It can be installed at 2, 3 or 4 inch spacing. The cable itself allows primary heating thanks to the twin-core ETFE cable, for highest output.

It comes with a lifetime warranty.



Operating voltage	120V, 208V or 240V
Thickness	3/16" (4.5mm - +/- 0.2mm)
Output	4W/lin foot approximately.
Construction	Multi-strand, dual conductor
Inner insulation	ETFE
Outer jacket	PVC, Hi Performance
Earth braid	Tin Plated Copper
Cold lead	10ft (3m)

The Perfectly Warm Heating Cable System is compatible with Schluter® DITRA-HEAT, Laticrete STRATA HEAT, Prodeso Heat Mat, Flextherm FLEXSnap, Heatmatrix, and Warmup DCM-PRO Membrane.

Product Code	Heating Cable Area (Sq. Ft.) (2-3 stud spacing - 3 stud spacing)	Heating Cable Length (Feet)	Heating Cable Length (Feet)	Average Power/SqFt (watts)
<b>120 Volt</b>				
PWW17-63W120V	Floor Heat Cable 4-5 Square Feet	17	4 - 5	13.5
PWW35-138W120V	Floor Heat Cable 9-11 Square Feet	35	9 - 11	13.5
PWW53-200W120V	Floor Heat Cable 13-16 Square Feet	53	13 - 16	13.5
PWW71-263W120V	Floor Heat Cable 18-21 Square Feet	71	18 - 21	13.5
PWW88-338W120V	Floor Heat Cable 22-27 Square Feet	88	22 - 27	13.5
PWW106-400W120V	Floor Heat Cable 27-32 Square Feet	106	27 - 32	13.5
PWW124-475W120V	Floor Heat Cable 31-38 Square Feet	124	31 - 38	13.5
PWW141-538W120V	Floor Heat Cable 36-43 Square Feet	141	36 - 43	13.5
PWW170-638W120V	Floor Heat Cable 43-51 Square Feet	170	43 - 51	13.5
PWW213-800W120V	Floor Heat Cable 54-64 Square Feet	213	54 - 64	13.5
PWW240-913W120V	Floor Heat Cable 61-73 Square Feet	240	61 - 73	13.5
PWW276-1038W120V	Floor Heat Cable 69-83 Square Feet	276	69 - 83	13.5
PWW303-1138W120V	Floor Heat Cable 76-91 Square Feet	303	76 - 91	13.5
PWW337-1275W120V	Floor Heat Cable 85-102 Square Feet	337	85 - 102	13.5
PWW372-1413W120V	Floor Heat Cable 94-113 Square Feet	372	94 - 113	13.5
PWW444-1675W120V	Floor Heat Cable 112-134 Square Feet	444	112 - 134	13.5



The Perfectly Warm™ Cable comes with a lifetime warranty covering the heating system, labour and materials. The Perfectly Warm™ warranty is industry leading.



# Perfectly Warm™

**Tile Floor Heat Cable** (for use with uncoupling membranes).

Product Code	Heated Area (2-3 stud spacing - 3 stud spacing)	Heating Cable Length (Ft)	Heating Cable Area (Feet)	Average Power/SqFt (watts)
<b>240 Volt</b>				
PWW35-138W240V	Floor Heat Cable 9-11 Square Feet	35	9 - 11	13.5
PWW53-200W240V	Floor Heat Cable 13-16 Square Feet	53	13 - 16	13.5
PWW71-263W240V	Floor Heat Cable 18-21 Square Feet	71	18 - 21	13.5
PWW88-338W240V	Floor Heat Cable 22-27 Square Feet	88	22 - 27	13.5
PWW106-400W240V	Floor Heat Cable 27-32 Square Feet	106	27 - 32	13.5
PWW124-475W240V	Floor Heat Cable 31-38 Square Feet	124	31 - 38	13.5
PWW141-538W240V	Floor Heat Cable 36-43 Square Feet	141	36 - 43	13.5
PWW176-675W240V	Floor Heat Cable 44-54 Square Feet	176	44 - 54	13.5
PWW212-813W240V	Floor Heat Cable 53-65 Square Feet	212	53 - 65	13.5
PWW248-950W240V	Floor Heat Cable 63-76 Square Feet	248	63 - 76	13.5
PWW282-1075W240V	Floor Heat Cable 71-86 Square Feet	282	71 - 86	13.5
PWW339-1288W240V	Floor Heat Cable 86-103 Square Feet	339	86 - 103	13.5
PWW426-1625W240V	Floor Heat Cable 107-130 Square Feet	426	107 - 130	13.5
PWW481-1838W240V	Floor Heat Cable 121-147 Square Feet	481	121 - 147	13.5
PWW551-2100W240V	Floor Heat Cable 139-168 Square Feet	551	139 - 168	13.5
PWW606-2313W240V	Floor Heat Cable 153-185 Square Feet	606	153 - 185	13.5
PWW674-2563W240V	Floor Heat Cable 170-205 Square Feet	674	170 - 205	13.5
PWW744-2838W240V	Floor Heat Cable 188-227 Square Feet	744	188 - 227	13.5

The Perfectly Warm™ Cable is a custom designed cable compatible with all uncoupling membranes. It can be installed at 2, 3 or 4 inch spacing. The cable itself allows primary heating thanks to the twin-core ETFE cable, for highest output.